

CM43

◆軸付き3軸

タイプ	外径(D)・長さ(T)・軸径(d)	使用限度回転数 (r.p.m)	
CM	43	4-13-3	20,000
CM	43	4-13-3	20,000
CM	43	6-17-3	20,000
CM	43	6-17-3	20,000
CM	43	8-15-3	40,000
CM	43	8-15-3	40,000
CM	43	10-15-3	40,000
CM	43	10-20-3	30,000
CM	43	10-20-3	30,000
CM	43	15-17-3	20,000
CM	43	6-17-3	15,000
CM	43	20-25-6	20,000
CM	43	20-40-6	15,000

CM43

◆軸付き6軸 軸長

タイプ	外径(D)・長さ(T)・軸径(d)	使用限度回転数 (r.p.m)	
CM	43	20-20-6(L=150)	5,000

CM43

◆平形

○100以下

タイプ	外径(D)・厚さ(T)・穴径(H)	使用限度回転数 (r.p.m)	
CM	43	15-3-1.8	18,000
CM	43	15-3-2	15,000
CM	43	15-4-1.8	10,000
CM	43	20-3-1.8	15,000
CM	43	20-3-2	15,000
CM	43	20-3-3	15,000
CM	43	20-4-2	15,000
CM	43	20-5-1.8	15,000
CM	43	22-3-1.8	15,000
CM	43	25-2-1.8	15,000
CM	43	25-3-1.8	15,000
CM	43	25-3-2	15,000
CM	43	25-5-3	15,000
CM	43	30-3-1.8	15,000
CM	43	30-3-3	15,000
CM	43	30-4-1.8	15,000
CM	43	30-5-3	15,000
CM	43	30-5-6	15,000
CM	43	30-6-3	15,000
CM	43	30-6-6	15,000
CM	43	35-10-6	12,000
CM	43	35-8-6	12,000
CM	43	40-4-3	9,000
CM	43	40-5-3	12,000
CM	43	40-8-6	12,000
CM	43	40-8-6	12,000
CM	43	40-10-6	12,000
CM	43	40-13-6	12,000
CM	43	45-10-6	9,000
CM	43	50-3-1.8	12,000
CM	43	50-4-6	9,000
CM	43	50-5-6	9,000
CM	43	50-6-6	9,000
CM	43	50-6-6	7,500
CM	43	50-8-6	9,000
CM	43	50-10-6	9,000
CM	43	50-13-6	9,000
CM	43	50-13-6	9,000
CM	43	50-15-6	9,000
CM	43	50-20-15.88	9,000
CM	43	60-10-6	8,000
CM	43	60-10-6	0
CM	43	60-4-6	10,000
CM	43	60-6-6	8,000
CM	43	65-6-6	7,500
CM	43	65-13-9.53	7,500
CM	43	65-13-9.53	7,500
CM	43	65-20-12.7	7,500
CM	43	65-20-12.7	7,500
CM	43	65-20-8	7,500
CM	43	75-10-6	6,000
CM	43	75-10-6	0
CM	43	75-13-9.53	6,000
CM	43	75-15-6	6,000
CM	43	75-15-9.0	6,000
CM	43	75-25-12.7	6,000
CM	43	75-4-6	6,000
CM	43	75-5-6	6,000
CM	43	75-8-6	6,000
CM	43	90-6-9.53	5,500
CM	43	90-8-9.53	5,500

CM55

◆軸付き3軸

タイプ	外径(D)・長さ(T)・軸径(d)	使用限度回転数 (r.p.m)	
CM	55	4-12-3	50,000
CM	55	4-13-3	30,000
CM	55	5-13-3	50,000
CM	55	5-13-3	50,000
CM	55	5-13-3	50,000
CM	55	5-13-3	50,000
CM	55	6-15-3	50,000
CM	55	6-15-3	50,000
CM	55	6-15-3	50,000
CM	55	6-17-3	30,000
CM	55	6-17-3	30,000
CM	55	13-25-6	20,000

CM55

◆平形

○100以下

タイプ	外径(D)・厚さ(T)・穴径(H)	使用限度回転数 (r.p.m)	
CM	55	10-2-1.8	15,000
CM	55	10-2-1.8	15,000
CM	55	10-3-1.8	15,000
CM	55	10-3-1.8	18,000
CM	55	11.9-4.5-1.8	18,000
CM	55	15-2-1.8	18,000
CM	55	15-2-1.8	18,000
CM	55	15-3-1.8	18,000
CM	55	15-4-1.8	18,000
CM	55	17-6-2-3	18,000
CM	55	20-1.5-1.8	18,000
CM	55	20-2-1.8	18,000
CM	55	20-2-2	18,000
CM	55	20-3-1.8	18,000
CM	55	20-3-1.8	18,000
CM	55	20-3-2	18,000
CM	55	20-4.5-1.8	18,000
CM	55	20-4-1.8	18,000
CM	55	22-3-1.8	18,000
CM	55	25-2.5-1.8	18,000
CM	55	25-2-1.7	18,000
CM	55	25-2-1.8	18,000
CM	55	25-2-1.8	15,000
CM	55	25-3-1.8	18,000
CM	55	25-3-3	18,000
CM	55	25-4-1.8	15,000
CM	55	25-4-3	18,000
CM	55	30-2-1.8	18,000
CM	55	30-2-1.8	15,000
CM	55	30-2-1.8	18,000
CM	55	30-3-1.8	18,000
CM	55	30-3-3	18,000
CM	55	30-4-3	18,000
CM	55	30-5-1.8	12,000
CM	55	30-5-3	18,000
CM	55	30-5-6	15,000
CM	55	40-4-1.8	14,400
CM	55	40-4-3	14,400
CM	55	40-4-3	90,000
CM	55	40-5-3	14,400
CM	55	50-4-6	11,500
CM	55	50-5-6	11,500
CM	55	75-2.5-6	7,500
CM	55	75-4-6	6,000

CMその他

◆軸付き3軸

タイプ	外径(D)・長さ(T)・軸径(d)	使用限度回転数 (r.p.m)		
A号	CMP	66	3-8-3	80,000
	CM	55X	4-12-3	50,000
	CM	55X	4-15-3	50,000
	CM	55X	6-15-3	50,000
	CM	55X	6-17-3	50,000
A号	CMK	(高速)	6-15-3	50,000
A号	CMK	(高速)	8-15-3	50,000
A号	CMK	(高速)	10-15-3	50,000

CM43

◆ 平形

○100以上

	タイプ	外径 (D)・厚さ (T)・穴径 (H)	使用限度回転数 (r.p.m)
CM	43	100-4-16.0	4,500
CM	43	100-8-8	4,500
CM	43	100-10-12.7	4,500
CM	43	100-10-6	4,500
CM	43	100-10-6	3,800
CM	43	100-10-8	4,500
CM	43	100-12-8	4,500
CM	43	100-13-12.7	4,500
CM	43	100-13-15.88	4,500
CM	43	100-13-9.53	4,500
CM	43	100-20-12.7	4500
CM	43	100-25-12.7	4,500
CM	43	芯金付 120-10-9.53	3,500
CM	43	125-15-15.88	3,500
CM	43	125-19-19.05	3,500
CM	43	125-6-12.7	3,500
CM	43	125-8-12.7	3,500
CM	43	125-8-25.4	3,500
CM	43	芯金付 150-10-12.7	3,000
CM	43	150-10-15.88	3,000
CM	43	両面補強 150-10-19.05	3,000
CM	43	150-10-19.05	3,000
CM	43	芯金付 150-10-19.05	3,000
CM	43	150-10-22.2	3,000
CM	43	芯金付 150-10-25.4	3,000
CM	43	150-10-25.4	3,000
CM	43	150-13-12.7	3,000
CM	43	150-13-15.88	3,000
CM	43	両面補強 150-13-19.05	3,000
CM	43	150-13-25.4	3,000
CM	43	150-13-9.53	3,000
CM	43	150-15-12.7	3,000
CM	43	150-15-15.88	3,000
CM	43	両面補強 150-15-19.05	3,000
CM	43	芯金付 150-15-19.05	3,000
CM	43	150-15-19.05	3,000
CM	43	150-15-22.2	3,000
CM	43	150-15-9.53	3,000
CM	43	150-20-12.7	3,000
CM	43	150-20-15.88	3,000
CM	43	両面補強芯金 150-20-19.05	3,000
CM	43	150-20-19.05	3,000
CM	43	芯金付 150-20-22.2	3,000
CM	43	150-20-8	3,000
CM	43	150-20-9.53	3,000
CM	43	150-25-15.88	3,000
CM	43	芯金付 150-25-25.4	3,000
CM	43	150-6-15.88	3,000
CM	43	180-20-19.05	2,500
CM	43	芯金付 180-40-76.2	2,500
CM	43	205-10-25.4	2,200
CM	43	芯金付 205-15-25.4	2,200
CM	43	両面補強芯金 205-20-19.05	2,200
CM	43	205-20-25.4	2,200
CM	43	205-25-76.2	2,200
CM	43	205-5-25.4	2,200
CM	43	両面補強芯金 255-15-25.4	1,800
CM	43	芯金付 255-15-25.4	1,800
CM	43	両面補強芯金 255-15-25.4	1,800
CM	43	両面補強芯金 255-20-25.4	1,800
CM	43	芯金付 255-20-25.4	1,800
CM	43	芯金付 255-25-19.05	1,800
CM	43	芯金付 255-25-25.4	1,800
CM	43	両面補強芯金 255-25-25.4	1,800
CM	43	両面補強 255-6-25.4	1,800
CM	43	両面補強芯金 305-13-25.4	1,500
CM	43	両面補強 305-6-25.4	1,500
CM	43	両面補強 305-9-25.4	1,500
CM	43	315-50-200	1,500

CM55

◆ 平形

○100以上

	タイプ	外径 (D)・厚さ (T)・穴径 (H)	使用限度回転数 (r.p.m)
CM	55	100-4-8	5,500
CM	55	150-10-12.7	3,500
CM	55	205-8-76.2	2,700
CM	55	両面補強 255-5-25.4	1,800

CMその他

◆ 平形

○100以上

	タイプ	外径 (D)・厚さ (T)・穴径 (H)	使用限度回転数 (r.p.m)
CM	43/4	125-15-15.88	4,500
CM	43/4	180-42-25	3,000
CM	43/4	補強ゴム付 360-28-180/120	1,600
CM	54/4	芯金付 255-32-19.05	2,200