

CM

◆ 平形φ100未満

下記サイズ・回転数は代表的なものです。下記以外のサイズにつきましてはお問い合わせください。

タイプ	外径 (D)-厚さ (T)-穴径 (H)	使用限度回転数 (r.p.m)	
CM	55	11.9-4.5-1.8	18,000
CM	55	15-2-1.8	18,000
CM	43	15-3-2	15,000
CM	55	15-4-1.8	18,000
CM	55	17-6.2-3	18,000
CM	55	20-1.5-1.8	18,000
CM	55	20-2-1.8	18,000
CM	55	20-3-1.8	18,000
CM	43	20-3-1.8	15,000
CM	43	20-3-2	15,000
CM	43	20-3-3	15,000
CM	55	20-4.5-1.8	18,000
CM	55	20-4-1.8	18,000
CM	43	20-4-2	15,000
CM	43	20-5-1.8	15,000
CM	43	22-3-1.8	15,000
CM	55	22-3-1.8	18,000
CM	55	25-2-1.7	18,000
CM	55	25-2-1.8	18,000
CM	55	25-2-1.8	15,000
CM	43	25-3-1.8	15,000
CM	55	25-3-1.8	18,000
CM	43	25-3-2	15,000
CM	55	25-3-3	18,000
CM	55	25-4-1.8	15,000
CM	55	25-4-3	18,000
CM	43	25-5-3	15,000
CM	55	30-2-1.8	18,000
CM	55	30-2-1.8	15,000
CM	55	30-3-1.8	18,000
CM	43	30-3-1.8	15,000
CM	55	30-3-3	18,000
CM	43	30-4-1.8	15,000
CM	55	30-5-1.8	12,000
CM	43	30-5-3	15,000
CM	55	30-5-3	18,000
CM	43	30-5-6	15,000
CM	43	30-6-6	15,000

CM	43	35-8-6	12,000
CM	43	40-10-6	12,000
CM	55	40-4-3	14,400
CM	43	40-5-3	12,000
CM	55	40-5-3	14,400
CM	43	40-8-6	12,000
CM	43	45-10-6	9,000
CM	43	50-10-6	9,000
CM	43	50-13-6	9,000
CM	43	50-4-6	9,000
CM	43	50-5-6	9,000
CM	55	50-5-6	11,500
CM	43	60-10-6	8,000
CM	43	65-13-9.53	7,500
CM	43	65-20-12.7	7,500
CM	43	65-20-8	7,500
CM	43	65-6-6	7,500
CM	43	75-10-6	6,000
CM	55	75-2.5-6	7,500
CM	55	75-4-6	6,000
CM	43	75-5-6	6,000
CM	43	75-8-6	6,000
CM	43	90-6-9.53	5,500
CM	43	90-8-9.53	5,500