

OX

◆ 平形φ100未満

下記サイズ・回転数は代表的なものです。下記以外のサイズにつきましてはお問い合わせください。

タイプ		外径 (D)-厚さ (T)-穴径 (H)	使用限度回転数 (r.p.m)
OX	55	10-3-3	18,000
OX	66	15-3-1.8	18,000
OX	55	15-3-1.8	18,000
OX	44	15-3-1.8	15,000
OX	44	15-3-2	15,000
OX	44	15-6-6	15,000
OX	44	18-1.5-1.8	15,000
OX	44	18-3-1.8	15,000
OX	66	20-1.5-1.8	18,000
OX	44	20-1.5-1.8	15,000
OX	44	20-2-1.8	15,000
OX	16	20-2-1.8	15,000
OX	44	20-2-1.8	12,000
OX	55	20-3-3	18,000
OX	44	22-1.5-1.8	15,000
OX	44	22-2-1.8	15,000
OX	44	22-3.2-3	15,000
OX	44	22-3-1.8	15,000
OX	44	25-1.5-1.5	15,000
OX	66	25-1.5-1.8	18,000
OX	44	25-1.5-1.8	15,000
OX	44	25-1-1	12,000
OX	44	25-1-1.8	15,000
OX	44	25-2-1.6	15,000
OX	44	25-2-1.8	15,000
OX	44	25-3.2-3	15,000
OX	66	25-3.2-3	18,000
OX	44	25-3.5-1.8	15,000
OX	44	25-3-1.8	15,000
OX	66S	25-3-1.8	18,000
OX	44	25-3-2	15,000
OX	55	25-3-3	18,000
OX	44	25-3-3	15,000
OX	44	25-3-4	15,000
OX	44	25-4-1.8	15,000
OX	66	25-4-1.8	18,000

OX	55	30-1.5-2	18,000
OX	44	30-2-1.8	15,000
OX	55	30-3.3-2	18,000
OX	44	30-3.9-3	15,000
OX	55	30-3-2	18,000
OX	33	30-4-2	12,000
OX	44	30-5-1.8	15,000
OX	66	30-5-3	18,000
OX	55	30-6-3	18,000
OX	0	30-8-6	12,000
OX	66	30-8-6 (5X)	18,000
OX	16	40-2-1.8	12,000
OX	16	40-3.2-3	12,000
OX	44	40-3-1.8	12,000
OX	44	40-4-3	12,000
OX	44	40-5-1.8	12,000
OX	77	40-5-15	12,000
OX	44	40-5-3	12,000
OX	44	45-8-6	12,500
OX	66	50-10-6	11,500
OX	66	50-2-2	12,500
OX	55	50-2-6	11,500
OX	44	50-3-1.8	9,000
OX	44	50-40-22.2	9,000
OX	33	50-4-6	7,600
OX	22	60-6-9.53	6,500
OX	66	60-6-9.53	6,500
OX	44	65-20-12.7	7,500
OX	66	75-2.5-6	7,500
OX	66	75-2-6	7,500
OX	66	75-2-9.53	7,500
OX	66	75-3-6	7,500
OX	66	75-4-6	7,500
OX	66	75-5-6	7,500
OX	66	90-2-9.53	6,000
OX	33	90-4-9.53	4,000
OX	22	90-4-9.53	4,000
OX	66	90-4-9.53	6,000
OX	16	90-4-9.53	5,500
OX	66	90-5-6.35	6,000
OX	22	90-6-9.53	4,000
OX	22	90-8-9.53	4,000