

CM

◆ 3 Shank

The sizes and rotational speeds shown below are representative examples.
Please contact us for sizes other than those listed below.

Shape	Type		Outer diameter (D) - Length (T) - Shank diameter (d)	Maximum rotation speed (r.p.m)
Shape-A	CM	55	3-13-3	20,000
Shape-A	CM	55	4-13-3	30,000
Shape-A	CM	55	5-15-3	30,000
Shape-A	CM	55	6-17-3	30,000
Shape-A	CM	55	6-20-3	20,000
Shape-A	CM	43	8-15-3	40,000
Shape-A	CM	43	8-20-3	30,000
Shape-A	CM	55	8-20-3	30,000
Shape-A	CM	43	10-15-3	40,000
Shape-A	CM	43	10-20-3	30,000
Shape-A	CM	55	10-20-3	30,000
Shape-A	CM	43	12-4-3	20,000
Shape-A	CM	43	13-15-3	20,000
Shape-A	CM	55	13-15-3	20,000
Shape-A	CM	43	13-20-3	20,000
Shape-A	CM	55	13-20-3	20,000
Shape-A	CM	43	13-4-3	20,000
Shape-A	CM	43	15-17-3	20,000
Shape-A	CM	55	15-20-3	15,000
Shape-A	CM	43	15-4-3	20,000
Shape-A	CM	55	15-4-3	20,000
Shape-A	CM	43	16-6-3	18,000
Shape-A	CM	43	20-10-3	15,000
Shape-A	CM	43	20-5-3	15,000
Shape-A	CM	43	20-6-3	15,000
Shape-A	CM	55	20-6-3	15,000
Shape-A	CM	43	25-6-3	12,000
Shape-A	CM	43	25-8-3	12,000
Shape-A	High-Speed Types		10-17-3	60,000
Shape-A	High-Speed Types		4-13-3	60,000
Shape-A	High-Speed Types		6-16-3	60,000
Shape-A	High-Speed Types		8-17-3	60,000

Shape	Type		Outer diameter (D) - Length (T) - Shank diameter (d)	Maximum rotation speed (r.p.m)
Shape-B	CM	43	20-3-3	20,000
	CM	43	25-3-3	18,000
	CM	55	25-3-3	18,000
	CM	43	30-3-3	12,000
	CM	55	30-3-3	12,000
	CM	43	30-6-3	12,000
Shape-E	CM	55	15-6-3(90°)	20,000
Shape-G	CM	55	6-17-3(G=90)	30,000
	CM	43	8-20-3(G=90)	30,000
Shape-K	CM	55	5-15-3	30,000
Shape-O	CM	55	4-13-3	30,000
	CM	55	5-15-3	30,000
	CM	55	6-17-3	30,000
	CM	43	8-20-3	30,000
	CM	43	10-20-3	30,000
	CM	43	13-20-3	20,000
Shape-R	CMP	66H	2d-3	50,000
	CMP	66H	2d-3(Normal Neck Type)	50,000
	CMP	66	3d-3	50,000
	CMP	66	2d-3(Normal Neck Type)	50,000
	CM	55	4d-3	30,000
	CM	55	5d-3	30,000
	CM	55	6d-3	30,000
	CM	43	8d-3	30,000
	CM	43	10d-3	30,000
	CM	55	10d-3	30,000
	CM	43	13d-3	20,000
	CM	55	13d-3	20,000
	CM	43	15d-3	20,000
	CM	55	15d-3	20,000