

## CM

### ◆Wheel Under Φ100

The sizes and rotational speeds shown below are representative examples.  
Please contact us for sizes other than those listed below.

| Type |    | Outside Diameter (D) - Thickness (T)<br>- Hole Diameter (H) | Maximum rotation speed (r.p.m) |
|------|----|-------------------------------------------------------------|--------------------------------|
| CM   | 55 | 11.9-4.5-1.8                                                | 18,000                         |
| CM   | 55 | 15-2-1.8                                                    | 18,000                         |
| CM   | 43 | 15-3-2                                                      | 15,000                         |
| CM   | 55 | 15-4-1.8                                                    | 18,000                         |
| CM   | 55 | 17-6.2-3                                                    | 18,000                         |
| CM   | 55 | 20-1.5-1.8                                                  | 18,000                         |
| CM   | 55 | 20-2-1.8                                                    | 18,000                         |
| CM   | 55 | 20-3-1.8                                                    | 18,000                         |
| CM   | 43 | 20-3-1.8                                                    | 15,000                         |
| CM   | 43 | 20-3-2                                                      | 15,000                         |
| CM   | 43 | 20-3-3                                                      | 15,000                         |
| CM   | 55 | 20-4.5-1.8                                                  | 18,000                         |
| CM   | 55 | 20-4-1.8                                                    | 18,000                         |
| CM   | 43 | 20-4-2                                                      | 15,000                         |
| CM   | 43 | 20-5-1.8                                                    | 15,000                         |
| CM   | 43 | 22-3-1.8                                                    | 15,000                         |
| CM   | 55 | 22-3-1.8                                                    | 18,000                         |
| CM   | 55 | 25-2-1.7                                                    | 18,000                         |
| CM   | 55 | 25-2-1.8                                                    | 18,000                         |
| CM   | 55 | 25-2-1.8                                                    | 15,000                         |
| CM   | 43 | 25-3-1.8                                                    | 15,000                         |
| CM   | 55 | 25-3-1.8                                                    | 18,000                         |
| CM   | 43 | 25-3-2                                                      | 15,000                         |
| CM   | 55 | 25-3-3                                                      | 18,000                         |
| CM   | 55 | 25-4-1.8                                                    | 15,000                         |
| CM   | 55 | 25-4-3                                                      | 18,000                         |
| CM   | 43 | 25-5-3                                                      | 15,000                         |
| CM   | 55 | 30-2-1.8                                                    | 18,000                         |
| CM   | 55 | 30-2-1.8                                                    | 15,000                         |
| CM   | 55 | 30-3-1.8                                                    | 18,000                         |

|    |    |            |        |
|----|----|------------|--------|
| CM | 43 | 30-3-1.8   | 15,000 |
| CM | 55 | 30-3-3     | 18,000 |
| CM | 43 | 30-4-1.8   | 15,000 |
| CM | 55 | 30-5-1.8   | 12,000 |
| CM | 43 | 30-5-3     | 15,000 |
| CM | 55 | 30-5-3     | 18,000 |
| CM | 43 | 30-5-6     | 15,000 |
| CM | 43 | 30-6-6     | 15,000 |
| CM | 43 | 35-8-6     | 12,000 |
| CM | 43 | 40-10-6    | 12,000 |
| CM | 55 | 40-4-3     | 14,400 |
| CM | 43 | 40-5-3     | 12,000 |
| CM | 55 | 40-5-3     | 14,400 |
| CM | 43 | 40-8-6     | 12,000 |
| CM | 43 | 45-10-6    | 9,000  |
| CM | 43 | 50-10-6    | 9,000  |
| CM | 43 | 50-13-6    | 9,000  |
| CM | 43 | 50-4-6     | 9,000  |
| CM | 43 | 50-5-6     | 9,000  |
| CM | 55 | 50-5-6     | 11,500 |
| CM | 43 | 60-10-6    | 8,000  |
| CM | 43 | 65-13-9.53 | 7,500  |
| CM | 43 | 65-20-12.7 | 7,500  |
| CM | 43 | 65-20-8    | 7,500  |
| CM | 43 | 65-6-6     | 7,500  |
| CM | 43 | 75-10-6    | 6,000  |
| CM | 55 | 75-2.5-6   | 7,500  |
| CM | 55 | 75-4-6     | 6,000  |
| CM | 43 | 75-5-6     | 6,000  |
| CM | 43 | 75-8-6     | 6,000  |
| CM | 43 | 90-6-9.53  | 5,500  |
| CM | 43 | 90-8-9.53  | 5,500  |